



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 Round bar
Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2
Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	38,0	
3,00 mm	h 7	0,1	(50,0)
4,00 mm	h 7	147,5	
5,00 mm	h 7	128,1	
6,00 mm	h 8	659,5	
8,00 mm	h 8	285,8	
10,00 mm	h 8	860,1	
12,00 mm	h 8	643,7	
14,00 mm	h 8	233,7	(200,0)
15,00 mm	h 8	406,2	
16,00 mm	h 9	1254,7	
18,00 mm	h 9	477,5	
20,00 mm	h 9	759,5	(300,0)
22,00 mm	h 9	888,7	
25,00 mm	h 9	294,5	(3000,0)
30,00 mm	h 9	692,1	
35,00 mm	h 9	1388,2	
40,00 mm	-0/+0.100	5,7	(1500,0)
45,00 mm	-0/+0.100	10,9	(1300,0)
50,00mm	-0/+0.100	279,3	(1730,0)
55,00 mm	-0/+0.100	1693,9	(3870,0)
60,00 mm	-0/+0.120	1749,2	(4278,0)
65,00 mm	-0/+0.120	840,1	(315,0)
70,00 mm	-0/+0.140	450,6	(300,0)
		0,0	(200,0)
80,00 mm	-0/+0.140	400,6	(300,0)
		0,0	(200,0)
90,00 mm	-0/+0.200	319,1	(500,0)
100,00 mm	-0/+0.500	492,5	(300,0)
		0,0	(234,0)
110,00 mm	-0/+0.500	381,1	(135,0)
		0,0	(282,0)
120,00 mm	-0/+0.500	620,3	
130,00 mm	-0/+0.500	16,3	(1438,3)
140,00 mm	-0/+0.500	282,8	(1000,0)
150,00 mm	-0/+0.500	524,9	(240,0)



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F67 / ISO 5832-2

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
160,00 mm	-0/+0.500	647,6	
170,00 mm	-0/+0.500	531,9	
180,00 mm	-0/+0.500	368,5	(345,0)
190,00 mm	-0/+0.500	347,9	
200,00 mm	-0/+0.500	318,4	(285,0)
225,00 mm	-0/+0.500	455,6	(360,0)
250,00 mm	-0/+0.500	296,6	(445,0)
280,00 mm	-0/+0.500	478,8	
305,00 mm	-0/+0.500	314,2	
305,00 mm	-0/+0.500	337,4	
350,00 mm	-0/+0.500	253,2	(435,0)

Titanium Grade 4 Round bar

Spec: ASTM B348 / ASME SB348 / ISO5832-2 / ASTM F67

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
100,00 mm	-0/+0.500	307,0	
130,00 mm	-0/+0.500	236,8	

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
2,00 mm	h 7	24,8	
3,00 mm	h 7	165,2	
4,00 mm	h 7	492,4	
5,00 mm	h 7	1139,7	(672,0)
6,00 mm	h 8	1907,3	(320,0)
8,00 mm	h 8	233,5	(427,0)
10,00 mm	h 8	237,6	(300,0)
12,00 mm	h 8	425,5	(710,0)
14,00 mm	h 8	361,2	
15,00 mm	h 8	369,5	
16,00 mm	h 9	1017,9	
18,00 mm	h 9	698,4	



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
20,00 mm	h 9	1676,0	
22,00 mm	h 9	73,9	(200,0)
25,00 mm	h 9	2360,0	(400,0)
25,00 mm	h 9	1130,6	
30,00 mm	h 9	78,4	(600,0)
35,00 mm	h 9	789,7	(900,0)
36,00 mm	h 9	1008,2	
40,00 mm	-0/+0.100	458,3	(700,0)
40,00 mm	-0/+0.100	458,3	(300,0)
		54,6	
45,00 mm	-0/+0.100	1272,3	(250,0)
50,00 mm	-0/+0.100	1775,1	
55,00 mm	-0/+0.100	402,5	(300,0)
60,00 mm	-0/+0.120	1073,9	(400,0)
65,00 mm	-0/+0.120	433,1	(500,0)
70,00 mm	-0/+0.140	537,3	
75,00 mm	-0/+0.140	1058,1	
80,00 mm	-0/+0.140	967,3	
		0,0	(200,0)
90,00 mm	-0/+0.200	399,6	
100,00 mm	-0/+0.500	337,2	(1410,0)
110,00 mm	-0/+0.500	144,5	(700,0)
120,00 mm	-0/+0.500	136,8	(600,0)
130,00 mm	-0/+0.500	647,1	(700,0)
140,00 mm	-0/+0.500	29,7	(1300,0)
150,00 mm	-0/+0.500	88,8	(700,0)
160,00 mm	-0/+0.500	772,5	
170,00 mm	-0/+0.500	88,1	(800,0)
180,00 mm	-0/+0.500	529,9	
190,00 mm	-0/+0.500	195,6	
200,00 mm	-0/+0.500	527,6	
225,00 mm	-0/+0.500	171,1	
230,00 mm	-0/+0.500	436,1	
250,00 mm	-0/+0.500	63,4	(445,0)
280,00 mm	-0/+0.500	398,0	(417,0)



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 5 Round bar

Spec: ASTM B348 / ASME SB348 / ASTM F136 ELI / ISO 5832-3 / AMS 4928

Condition: annealed, centerless ground

Dia in mm	Tol.	QTY (kg)	Incoming
305,00 mm	-0/+0.500	396,4	
330,00 mm		360,4	
350,00 mm	-0/+0.500	289,6	(440,0)

Titanium Grade 1 sheets

Spec: ASTM B265 GR1 edition 2015 / ASME SB 265 Gr1 edition 2015 DIN 17860 / NACE

MR0175/ PED 2014/68/EU / AL 111 4890-63 rev. 13

Contidtion: cold/hot rolled, annealed

Dimension	QTY (kg)	Incoming
	4,9	(197,4)
0,6 x 1000 x 2500	14,1	(600,0)
0,8x 1000 x 2500	808,4	(900,0)
1,0 x 1250 x 3000	811,8	(1800,0)
1,5 x 1250 x 3000	346,0	(400,0)
2,0 x 1250 x 3000	203,2	
2,0 x 1250 x 3000	1262,2	(2000,0)
2,5 x 1250 x 3000	212,6	
3,0 x 1250 x 3000	1066,9	
4,0 x 1000 x 2000	452,1	
	796,5	
5,0 x 1000 x 2000	468,4	
6,0 x 1000 x 2000	508,6	

Titanium Grade 2 sheets

Spec: ASTM B265 GR2 -2015 / ASME SB 265 GR2 -2017

PED 2014/68/EU/ NACE MR0175

Condition: cold/hot rolled, annealed, polished

Dimension	QTY (kg)	Incoming
1,0x1000x2000	275,9	
	54,4	
1,0x1000x2000	8,2	
1,5x1000x2000	229,4	(297,0)
	203,0	(169,0)
	188,7	(105,8)
2,0x1000x2000	291,2	(198,0)
3,0x1000x2000	156,7	(297,0)
4,0x1000x2000	157,7	(828,0)
5,0x1000x2000	365,8	



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 sheets

Spec: ASTM B265 GR2 -2015 / ASME SB 265 GR2 -2017

PED 2014/68/EU/ NACE MR0175

Condition: cold/hot rolled, annealed, polished

Dimension	QTY (kg)	Incoming
6,0x1000x2000	0,0	(216,0)
	0,0	(202,0)
8,0x1500x2500	0,0	(450,0)

Titanium Grade 5 sheets

Spec: ASTM B265/ASME SB265

Condition: cold/hot rolled, annealed, grinded surface

Dimension	QTY (kg)	Incoming
1 x 1000 x 2000	176,8	
1 x 1000 x 2000	150,8	
1 x 1000 x 2000	13,5	
	171,9	(180,6)
	215,6	(216,8)
	282,9	(135,4)
2 x 1000 x 2000	120,0	(200,0)
	349,8	(180,5)
	188,6	(225,7)
3 x 1000 x 2000	231,8	
3 x 1000 x 2400	302,1	
3 x 1250 x 2500	43,2	
	213,8	(270,8)
4 x 1000 x 2000	70,4	(216,0)
	0,0	(365,7)
5 x 1000 x 2000	35,6	(315,0)
	0,0	(450,5)
	102,7	(108,4)
	0,0	(150,5)

Titanium Grade 2 Profiles

Spec: ASTM B265

Condition: hot rolled, annealed, straight, black and sandblasting surface

Dimension	QTY (kg)	Incoming
9,5 x 9,5	91,7	
12,7 x 12,7	219,0	



TITANIUM GATEWAY

STOCK & SALES - TITANIUM & SPECIAL ALLOYS

Titanium Grade 2 Profiles

Spec: ASTM B265

Condition: hot rolled, annealed, straight, black and sandblasting surface

Dimension	QTY (kg)	Incoming
19,05 x 19,05	249,7	
25,4 x 6,35	141,3	
25,4 x 12,7	39,4	
25,4 x 25,4	0,3	(500,0)

Titanium Grade 2 Welding wire

AWS A5.16 ERTi-2

Dimension	QTY (kg)	Incoming
1,2 mm	40,0	
1,2 mm	20,0	
2,0 mm	35,0	
2,4 mm	50,0	
3,2 mm	50,0	

Titanium Grade 5 Welding wire

AWS A5.16 ERTi-5

Dimension	QTY (kg)	Incoming
1,6 mm	10,0	
2,4 mm	10,0	